


ACOUSTIC
FELT



FeltVibe®



GENTUĞ



PET Felt Acoustic Panels


ARKETA Collections (Base Material)

PRODUCT SHEET

PET Felt Acoustic Panels

ARKETA Collections (Base Material)


ARKETA
 Acoustic Felt Panel
 (Base Material)




ARKETA is a high-performance sound absorber with a layered construction allowing for a high degree of variation in thickness, density, and acoustical performance. Available in 5 standard neutral colors, ARKETA can be combined with any ARKETA acoustic felt layers (on one or two sides) to make up a high performance SATIS acoustical sheet.

For industrial settings (such as ecommerce distribution warehouses) ARKETA can be ordered 'naked' (without an SATIS surface) and mounted directly on walls and ceilings without any spacing and achieves absorption levels of up to 0.42 NRC (subject to thickness/density ordered). ARKETA has a natural 'skin' on the surface to allow for easy cleanability. ARKETA is made up of 100% PET fiber, of which at least 60% comes from recycled plastic bottles, making it a sustainable acoustic panel that provides amazing value, and acoustical performance.


THICKNESS OPTIONS




3mm
 550 g/m²




6mm
 Min. 800 g/m²
 Max. 1300 g/m²




7mm
 Min. 900 g/m²
 Max. 1300 g/m²



8mm
 Min. 1000 g/m²
 Max. 1300 g/m²







9mm
 Min. 1100 g/m²
 Max. 1300 g/m²



11mm
 1800 g/m²





Arketa White

Arketa Light Grey

Arketa Pure Grey

Arketa Dark Grey

Arketa Black

SPECIFICATIONS

COMPOSITION	60% Recycled Polyester (PET) (100% Pes)
DIMENSIONS	Max. Width: 2000mm
COLOR	5 color
THICKNESS / WEIGHT	3mm (±0.5mm) / 550 g/m ² (±10%) 6mm (±0.5mm) / min. 800 g/m ² (±10%) 6mm (±0.5mm) / max. 1300 g/m ² (±10%) 7mm (±0.5mm) / min. 900 g/m ² (±10%) 7mm (±0.5mm) / max. 1300 g/m ² (±10%) 8mm (±0.5mm) / min. 1000 g/m ² (±10%) 8mm (±0.5mm) / max. 1300 g/m ² (±10%) 9mm (±0.5mm) / min. 1100 g/m ² (±10%) 9mm (±0.5mm) / max. 1300 g/m ² (±10%) 11mm (±0.5mm) / 1800 g/m ² (±10%)
ACOUSTIC	NRC: up to 0.42 Class E (subject to mounting conditions)
THERMAL RESISTANCE	0.0446 W/m ² K, ISO 110902:2014
FIRE TEST STANDARDS	EN 1021 - 1 (cigarette) EN 13501-1 (SBI) Adhered Class B-s1,d0
LIGHT FASTNESS	4+ (ISO 105 - B02)
ENVIRONMENT	%60 recycled PET Non VOCs emission formaldehyde free and Phenol-free Oekotex Class 1, Phthalate Free
CLEANNING	Vacuum regularly. Professionally dry clean or wipe clean with a dampcloth.
GENERAL	Tackable, impact resistant, bacteria resistant, moisture resistant, installation friendly.



HEAD OFFICE

Savaş Cad. Söğüt Sok. No: 1
34164 Merter, İstanbul, Türkiye
T: +90 212 637 09 89
F: +90 212 637 02 96
info@feltvibe.com

DÜZCE FACTORY

Organize Sanayii Bölgesi 13. Ada
1/4 Parsel Beyköy Belediyesi
81060 Düzce, Türkiye
T: +90 380 553 73 68-69
F: +90 380 553 73 68-69

GEREDE FACTORY

Gerkonsan Organize
Sanayii Bölgesi
14900 Gerede, Bolu, Türkiye
T: +90 374 311 82 57 / 58
F: +90 374 311 66 37

İZMİR BRANCH

MTK Sitesi 747/ 2 Sokak
No:37 6003 ADA, 6003
Altındağ, İzmir, Türkiye
T: +90 232 431 08 17-18
F: +90 232 431 08 19

FOLLOW US



www.feltvibe.com